

CHAIN TRENCHERS

CHD 90
CHD 120
CHD 150



CHD Chain Trenchers are designed for set-section trenching on soft soils.

The discharge screw on the righthand side and the trench clearing device makes sure the trench is kept clean, while the slide provides maximum stability at any trenching depth.

Chain is available with hoe blades for soft soils or hoe blades with teeth for mixed soils.

SIMEX **PERFORMER**
• patent •



ADVANTAGES

- Clean trench
- Maximum stability at any depth

TECHNICAL DATA		CHD 90	CHD 120	CHD 150
Max. trench depth	mm inch	900 35	1200 47	1500 59
Trench width - standard	mm inch	150 6	150 6	150 6
Trench width - optional	mm inch	200 - 250 8 - 10	200 - 250 8 - 10	200 8
Side shift		standard - hydraulic (optional)		
Scraper		mechanical spring-operated		
Operating weight (1)	kg lbs	715 1575	780 1715	830 1830
Required oil flow	l/min gmp	60 - 120 16 - 32	70 - 140 18 - 37	90 - 160 24 - 42
Max. oil pressure	BAR psi	250 3625	250 3625	250 3625

(1) User is responsible for ensuring that the characteristics of the prime mover suit the weight and specifications of the attachment. Simex does not accept responsibility or liability for the information provided. Technical modifications may vary without prior notice.



Utilities
Quarries and mines

Demolition

Port and underwater works

Construction and building

Infrastructure

Tunneling

Agriculture and forestry

Recycling

Roadworks

Trenching

Mini-excavator

Excavator

Skid steer loader

Front loader

Backhoe