

TECHNICAL DATA

TAMPER

BT 80 D



High level of reliability
Corrosion-resistant fuel tank




Low CO2 emissions
Yanmar diesel engine



Simple operation
Engine control via lever (on/off/speed)

Shipping dimensions in m3

BT 80 D 0,289



Standard Equipment

- Vibration insulated steering handle
- Integrated fuel filter
- Protective engine covering
- Single lever for on/off/speed adjustment
- Infinitely variable frequency
- Single point lifting device
- Semi-automatic decompression
- Recoil starter
- 3-2-1 Warranty

Optional Equipment

- Transport device with puncture proof wheels
- Tool kit
- Service Kit

Dimensions in mm

	B	H	L	L1	W
BT 80 D	370	1056	740	340	330

Technical Data

**BOMAG
BT 80 D**

Weights

Basic weight	kg	85
Operating weight CECE	kg	86

Dimensions

Working width (tamper plate)	mm	330
------------------------------------	----	-----

Driving Characteristics

Working speed max.	m/min	9
-------------------------	-------	---

Drive

Engine manufacturer	Yanmar
Type	L48V6
Emission stage	Stage V
Cooling	air
Number of cylinders	1
Performance SAE J 1349	kW 3,4
Speed	min-1 3.600
Fuel	Diesel
Drive system	mech.
Fuel comsump. aver. during operation	l/h 0,8

Exciter system

Frequency	Hz	7,7- 11,1
Impact force	kN	21,0

Capacities

Fuel	l	3,4
------------	---	-----

Technical modifications reserved. Machines may be shown with options.



PRE 540 65 010

230223 Sa01

BOMAG
Hellerwald
D-56154 Boppard
P.O. Box 5162
Tel. (0)6742 - 1000
Fax (0)6742 - 3090

