



# Excavator mulcher

TCB / TCM / TCS / TCE / TCR



## Technical Specification



**Excavator mulcher** to top grass and mulch bushes, brambles, shrubs and underwood suitable for excavators and backhoes.




**Leveling roller** for adjustment of cutting height.

**Side skids** with replaceable runners.

**Self leveling support** with smooth plate (pin bracket for excavator on request).

**Completely closed structure** for protection. Different types of tools available (on request).

# Excavator mulcher

		TCB	TCM		TCS		TCE		TCR			
MODEL		60	60	80	80	100	90	110	95	115	125	
<b>Technical specification</b>	um											
Working width	mm	600	600	800	800	1000	900	1100	950	1150	1250	
Oil flow, min-max	mm	18-20	32-40		35-45		50-60		65-75			
Oil pressure, min-max	bar	180-200	180-220		180-220		200-220		200-220			
Weight standard configuration	kg	100	175	200	245	275	440	470	440	480	495	
Max cutting	Ø mm	20	30		30		40		50			
Blade	n.	10	-		-		-	-	-	-	-	
Hammer	n.	10	8	12	12	16	12	16	8	10	12	
	ton	1,5-2,5	2,5-3,5		3,5-5,5		5,5-8,0		7,0-9,0			
	ton	-	-		-		6,0-9,0		8,0-10,0			
	Overall size in standard configuration	A cm	63	90	110	95	115	90	110	115	135	145
		B cm	55	60	60	58	58	60	60	69	69	88
		C cm	65	75	75	84	84	75	75	94	94	94



Data, descriptions and images of this document are not binding hence GF Gordini reserves the right to alter part or all of them at any time with no notice.

## ACCESSORIES FOR OPERATING MACHINES



Via E. Mattei, 4 - 48012 Bagnacavallo RA - Italy  
tel +39 0545 62712 fax +39 0545 62140  
info@gfgordini.com - www.gfgordini.com

**YOUR BEST CHOICE SINCE 1985.**

