

R164 (ST5)

COMPACT LOADERS



KEY FEATURES

- ✓ PowerView® Boom Lift Arm - Radial
- ✓ Hydraloc™ System
- ✓ Level II ROPS/FOPS
- ✓ Dual T-Bar, Joystick and Hand/Foot Controls available
- ✓ Cushion Seat
- ✓ Battery Charge Indicator Lamp
- ✓ Hourmeter
- ✓ Vandalism Lock Provisions - Fuel and Engine Cover

KEY SPECIFICATIONS

- ✓ Operating Capacity (50%) - 748 kg (1,649 lbs.)
- ✓ Overall height to top of ROPS - 1948 mm (77")
- ✓ Gross Power - 69.3 hp (51.7 kW) @ 2500 rpm
- ✓ Yanmar 4TNV98C, Stage V Engine
- ✓ 241.3 Nm (178.8 ft.-lbs) @ 1625 rpm max torque
- ✓ 3023 mm (119") height to hinge pin
- ✓ 1582 mm (62") machine width - less bucket
- ✓ 2792 kg (6,155 lbs.) operating weight

METRIC		
CAPACITIES	Rated Operating Capacity	748 kg
	Unladen weight	2792 kg
	Tipping capacity	1496 kg
WEIGHT AND DIMENSIONS	Wheelbase	988 mm
	Overall Operating Height - Fully Raised	3876 mm
	Height to Hinge Pin - Fully Raised	3023 mm
	Overall Height to top of ROPS	1948 mm
	Dump angle at full height	38 °
	Dump height	2379 mm
	Overall length with bucket	3101 mm
	Dump reach - Full height	579 mm
	Rollback at ground	28 °
	Rollback Angle at Full Height	99 °
	Seat to ground height	930 mm
	Overall width less bucket	1582 mm
	Bucket Width	1562 mm
	Ground clearance	160 mm
	Overall length - Less Bucket	2390 mm
PERFORMANCES	Travel speed (unladen)	12.60 km/h
	Travel Speed with Two-Speed Option - Maximum	19.50 km/h
	Standard tires	10 x 16.5 - 10 PR HD
ENGINE	Engine brand	Yanmar
	Engine model	4TNV98C
	Engine nom	Stage V
	Max. torque / Engine rotation	241.30 Nm / 2500 rpm
	Power source	Diesel
	Number of cylinders	4
	Engine power (Hp / kW)	68.40 Hp / 51 kW
	Battery voltage	12 V
	Accessory plug	12 V
	Alternator - Ampere	100 A
HYDRAULICS	Standard flow - Auxiliary hydraulics	71.40 l/min
	Auxiliary Hydraulic Pressure	207 bar
	High-Flow Auxiliary Hydraulics - Option	114 l/min
TANK CAPACITIES	Fuel tank capacity	62.50 l
	Hydraulic tank capacity	41.60 l
	Displacement	3.30 l
	LH Chain case	8.50 l
	RH Chain case	8.50 l

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- All-Tach® Attachment Mounting System
- Automatic engine shutdown
- Auxiliary Hydraulics
- Foot and Hand Throttles (Dual Joystick and T-bar)
- Front and Rear - Work Lights
- High-Back Adjustable Seat
- Horn
- Servo-Controlled Hydrostatic Drive
- Swing-Out Cooler
- Hydraloc™ Safety System
- Lift Arm Support Device
- Anti-Vandalism Protection
- Brake Control (Auto / Manual)
- Sound Reduction Material
- ROPS/FOPS Level II Overhead Guard
- Full Instrumentation
- Operator Restraint Bar
- Integral Access Plate (removable)

OPTIONAL FEATURES

- Back-Up Alarm
- Hand/Foot Controls
- Pressurized Cab Enclosure with A/C
- T-Bar Controls
- Selectable Self-Leveling Hydraulic Lift Action 4
- Engine Block Heater



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT