



RANGE

PL

STABILIZERS

SELF-LEVELLING

PL 60.25

PL 100.25

- Constant depth
- Excellent mixing
- Maximum safety
- Stability and no vibrations
- Optimal visibility for the operator

STABILIZERS

SELF-LEVELLING

PL 60.25
PL 100.25



Simex PL self-levelling road stabilizers are designed to perform ground stabilization and consolidation. Excellent for consolidating sub-layers and ideal for mixing material with lime or cement. Work at a profound depth (250mm).

Thanks to the exclusive self-levelling system, milling depth is constant in any condition. Stabilizers feature transverse tilt, side shift, and independent RH-LH depth adjustment.

SIMEX **PERFORMER**
• patent •

ADVANTAGES

- Constant depth
- Excellent mixing
- Maximum safety
- Stability and no vibrations
- Optimal visibility for the operator

TECHNICAL DATA		PL 60.25	PL 100.25
Standard drum			
Width	mm inch	600 24	1000 40
Depth	kg lbs	0 - 220 0 - 8,5	0 - 220 0 - 8,5
Special drums			
Max. depth with reduced width	mm inch	250 10	250 10
Depth adjustment		independent RH/LH, mechanical - hydraulic (optional)	
Side shift		hydraulic	hydraulic
Transverse tilt		Autom/Hyd.*	Autom/Hyd.*
Tilt		16°	16°
Weight standard version (1)	kg lbs	1200 2640	1650 3630
Required oil flow	l/min gpm	110 - 170 29 - 45	120 - 190 32 - 50
Max. oil pressure	BAR psi	300 4350	300 4350

(1) User is responsible for ensuring that the characteristics of the prime mover suit the weight and specifications of the attachment.

(*) On request

Simex does not accept responsibility or liability for the information provided. Technical modifications may vary without prior notice.



- Utilities
- Quarries and mines
- Demolition
- Port and underwater works
- Construction and building
- Infrastructure
- Tunneling
- Agriculture and forestry
- Recycling
- Roadworks
- Trenching
- Mini-excavator
- Excavator
- Skid steer loader
- Front loader
- Backhoe