



SIMEX
HEAVY MADE EASY

RANGE
MP

CUTTER HEADS FOR PROFILING



- Perfect finish
- Constant milling depth
- Milling on horizontal, vertical or sloped surfaces
- Ideal for profiling applications

CUTTER HEADS FOR PROFILING

MP 800
MP 1000



Simex MP cutter heads for profiling, designed for excavator boom mounting, guarantee precision finishing in applications such as: resurfacing tunnel roofs, rehabbing deteriorated surfaces, concrete embankments and industrial pavements.

Wheels or lateral slides allow milling thickness to remain constant in any condition. Excellent for materials such as **asphalt, concrete** and **rock**, and for milling **on horizontal, vertical or sloped surfaces**.

Wall alignment device (*Optional*).



ADVANTAGES

- Perfect finish
- Constant milling depth
- Milling on horizontal, vertical or sloped surfaces
- Ideal for profiling applications

TECHNICAL DATA		MP 800	MP 1000
Recommended excavator weight (1)	ton lbs	22 - 40 48500 - 88000	22 - 40 48500 - 88000
Milling width	mm inch	800 31	1000 40
Max. working depth	mm inch	100 4	100 4
Cutting force	kN lbf	43,8 9850	43,8 9850
Operating weight (2)	kg lbs	2000 4400	2300 5060
Required oil flow	l/min gpm	200 - 300 53 - 80	200 - 300 53 - 80
Max. required oil pressure	BAR psi	350 5100	350 5100

(1) User is responsible for ensuring that the equipment meets the excavator's specifications and weight requirements.
(2) Without mounting bracket.

Simex does not accept responsibility or liability for the information provided. Technical modifications may vary without prior notice.



- Utilities
- Quarries and mines
- Demolition
- Port and underwater works
- Construction and building
- Infrastructure
- Tunneling
- Agriculture and forestry
- Recycling
- Roadworks
- Trenching
- Mini-excavator
- Excavator
- Skid steer loader
- Front loader
- Backhoe