



RANGE

CT

VIBRATING WHEEL COMPACTORS

CT 2.8B

- Extremely precise and versatile
- Maximum operator comfort
- Result: solid, even and well compacted trench bottom

VIBRATING WHEEL COMPACTORS

CT 2.8B



Designed for compacting trench bottoms, Simex CT vibrating wheel compactors guarantee a permanently solid, even and well compacted **bottom** that ensures maximum road safety. Perfect insulation from prime mover. Thanks to the reverse-rotation vibrating twin shaft positioned at center of the wheel, vertical forces are added up and horizontal forces are countered for increased operator comfort.

Wheel width can be adjusted via bolted sectors that are easily changed on site. Possibility to mount the rotation allows

compaction in any position, even in the most difficult-to-reach areas.

ADVANTAGES

- Extremely precise and versatile
- Maximum operator comfort
- Result: solid, even and well compacted trench bottom

TECHNICAL DATA			CT 2.8B
Recommended excavator weight (1)		ton lbs	5 - 12 11000 - 26500
Standard wheel			
Width of bolted sectors (mm)		mm inch	150 - 200 - 250 - 300 - 350 - 400 6 - 8 - 10 -12 -14 - 16
Working depth		mm inch	0 - 700 <i>0 - 28</i>
Special wheels			
Wheel width (2)		mm inch	50 - 100 2 - 4
Working depth		mm inch	0 - 350 <i>0 - 14</i>
Vibration frequency		Hz	30 - 40
Max. vertical force		kN /bf	42 9400
Operating weight (3)		kg Ibs	530 - 585 1160 - 1300
Required oil flow	· ·	/min gpm	40 - 60 11 - 16
Max. required oil pressure		BAR psi	220 3200

- (1) The maximum operating load permitted for the excavator, when added to the weight of the standard bucket, must match or exceed the weight of the attachment. (2) User is responsible for ensuring that the equipment meets the excavator's specifications and weight requirements. (3) Widths different from those indicated are available on request.
- Simex does not accept responsibility or liability for the information provided. Technical modifications may vary without prior notice.



