



**YANMAR**

MINI EXCAVATOR

**ViO17**



**Weight**

Operating weight 1765 kg  
 Transport weight 1690 kg

**Engine**

Type Yanmar 3TNV70-XBV  
 Fuel Diesel  
 Displacement 854 cm<sup>3</sup>  
 Maximum torque 52 N.m. / 1600 tr/min  
 Net power 10,1 kW

**Performance**

Travelling speed 2,1 / 4,3 km/h  
 Rotation speed 9,5 rpm  
 Digging force (arm) 8,53 kN  
 Digging force (bucket) 15,2 kN  
 Grade ability 30°  
 Noise level 93 dB(A)  
 (2000/14/CE & 2005/88/CE)

**Hydraulic system**

Maximum pressure 170 bar  
 2 variable displacement piston pumps 2 x 17,6 l/min  
 1 gear pump 13,2 l/min

**Undercarriage**

Ground pressure 0,29 kg/cm<sup>2</sup>

**Capacities**

Fuel tank 20 l  
 Cooling fluid 3,2 l

**Standard equipment**

Canopy ROPS  
 Road protection for boom arm and bucket cylinders  
 Proportional 3rd hydraulic circuit line to arm end  
 Comfort seat  
 Extendable undercarriage (950 - 1280 mm)  
 Grease pump and toolbox

**Optional equipment**

Prolongation of the 3rd circuit to arm end  
 Quick couplers on the 3rd circuit  
 Mechanical quick hitch  
 Anti-theft device (with key / keyboard)  
 Standard, ditch cleaning and swivelling buckets  
 Hydraulic breaker  
 Beacon light

**Dimensions**

